


BT-W

WELDON END MILL HOLDERS



Application:
For mounting straight-shank tools with flat according to DIN 1835 form B (Weldon).



MAS 403 BT

JIS B 6339



Form AD/B

$\nabla \leq 0,003$

G6,3
15.000 min⁻¹

Order no.	Taper	dH4	A	D
BT.40ADB-W.16.035	BT 40	16	35	45
BT.40ADB-W.20.035	BT 40	20	35	45
BT.40ADB-W.25.035	BT 40	25	35	55
BT.40ADB-W.32.065	BT 40	32	65	50
BT.40ADB-W.06.050	BT 40	6	50	25
BT.40ADB-W.08.050	BT 40	8	50	28
BT.40ADB-W.10.063	BT 40	10	63	35
BT.40ADB-W.12.063	BT 40	12	63	42
BT.40ADB-W.14.063	BT 40	14	63	44
BT.40ADB-W.16.063	BT 40	16	63	48
BT.40ADB-W.18.063	BT 40	18	63	50
BT.40ADB-W.20.063	BT 40	20	63	52
BT.40ADB-W.25.090	BT 40	25	90	65
BT.40ADB-W.32.100	BT 40	32	100	72
BT.40ADB-W.40.120	BT 40	40	120	80
BT.40ADB-W.06.100	BT 40	6	100	25
BT.40ADB-W.08.100	BT 40	8	100	28
BT.40ADB-W.10.100	BT 40	10	100	35
BT.40ADB-W.12.100	BT 40	12	100	42
BT.40ADB-W.14.100	BT 40	14	100	44
BT.40ADB-W.16.100	BT 40	16	100	48
BT.40ADB-W.18.100	BT 40	18	100	50
BT.40ADB-W.20.100	BT 40	20	100	52
BT.40ADB-W.06.160	BT 40	6	160	25
BT.40ADB-W.08.160	BT 40	8	160	28
BT.40ADB-W.10.160	BT 40	10	160	35
BT.40ADB-W.12.160	BT 40	12	160	42
BT.40ADB-W.14.160	BT 40	14	160	44
BT.40ADB-W.16.160	BT 40	16	160	48
BT.40ADB-W.18.160	BT 40	18	160	50
BT.40ADB-W.20.160	BT 40	20	160	52
BT.40ADB-W.25.160	BT 40	25	160	65
BT.40ADB-W.32.160	BT 40	32	160	72
BT.40ADB-W.40.160	BT 40	40	160	80

DIN 69871

ISO 60

MAS 403 BT

DIN 2080

HSK-A

VDI

MORSE

