


BT-FMH1

SHELL MILL HOLDERS



Application:
For mounting milling cutters with transversal groove.



MAS 403 BT

JIS B 6339



$\nabla \leq 0,005$

G6.3
15.000 min⁻¹

Order no.	Taper	dh6	A	l ₁	D
BT.30AD-FMH1.16.040	BT 30	16	40	17	38
BT.30AD-FMH1.22.040	BT 30	22	40	19	48
BT.30AD-FMH1.27.040	BT 30	27	40	21	58
BT.30AD-FMH1.32.050	BT 30	32	50	24	78
BT.40ADB-FMH1.16.040	BT 40	16	40	17	38
BT.40ADB-FMH1.22.040	BT 40	22	40	19	48
BT.40ADB-FMH1.27.040	BT 40	27	40	21	58
BT.40ADB-FMH1.32.050	BT 40	32	50	24	78
BT.40ADB-FMH1.40.050	BT 40	40	50	27	88
BT.40ADB-FMH1.16.100	BT 40	16	100	17	38
BT.40ADB-FMH1.22.100	BT 40	22	100	19	48
BT.40ADB-FMH1.27.100	BT 40	27	100	21	58
BT.40ADB-FMH1.32.100	BT 40	32	100	24	78
BT.40ADB-FMH1.40.100	BT 40	40	100	27	88
BT.40ADB-FMH1.16.160	BT 40	16	160	17	38
BT.40ADB-FMH1.22.160	BT 40	22	160	19	48
BT.40ADB-FMH1.27.160	BT 40	27	160	21	58
BT.40ADB-FMH1.32.160	BT 40	32	160	24	78
BT.40ADB-FMH1.40.160	BT 40	40	160	27	88

BT 30 without coolant exit bores on the end face d = 40:

For large diameter face mill cutters with four additional threaded holes according to DIN 2079.

Delivery: With drivers, cross head retaining screw and cylinder head retaining screw for cutters with central coolant.

