


Countersink 90° with irregular pitch, DIN 335-C

- ▲ all sizes with 3 cutting edges and highly irregular pitch, resulting in smooth running, excellent roundness and chatter reduction giving the highest surface quality
- ▲ for very high tool life in almost all materials
- ▲ greatly reduced axial and radial forces
- ▲ for countersinking to DIN ISO 7721 and DIN 7991

N



NEW

TiN

SIG 90°
HSS

30 141 ...

DC_2 ₂₅ mm	DC_1 mm	DCONMS _{H9} mm	OAL mm	DIN ISO 7721	DIN 7991	
4,3	1,3	4	40	M2		04300
6,0	1,5	5	45	M3		06000
6,3	1,5	5	45		M3	06300
8,0	2,0	6	50	M4		08000
8,3	2,0	6	50		M4	08300
10,0	2,5	6	50	M5		10000
10,4	2,5	6	50		M5	10400 ¹⁾
11,5	2,8	8	56	M6		11500
12,4	2,8	8	56		M6	12400
15,0	3,2	10	60	M8		15000
16,5	3,2	10	60		M8	16500 ¹⁾
19,0	3,5	10	63	M10		19000
20,5	3,5	10	63		M10	20500
23,0	3,8	10	67	M12		23000
25,0	3,8	10	67		M12	25000 ¹⁾
31,0	4,2	12	71		M16	31000

P	●
M	○
K	●
N	●
S	○
H	○
O	○

1) Included in the set

→ v. Page 91

Countersink 90° with irregular pitch, DIN 335-C – Set

Scope of supply:

Countersinks Ø 10.4 / 16.5 / 25.0 mm in storage case

N



NEW

TiN

30 141 ...

99900