


BT-CC-ER

COLLET CHUCKS - ER



Application:
For mounting straight-shank tools in collets.



MAS 403 BT

JIS B 6339



Form AD

$\nabla \leq 0,003$

G6,3
15.000 min⁻¹

Order no.	Taper	Range	A	D
BT.30AD-CC.ER16.070	BT 30	1 – 10 (ER 16)	70	32
BT.30AD-CC.ER25.070	BT 30	2 – 16 (ER 25)	70	42
BT.30AD-CC.ER32.070	BT 30	2 – 20 (ER 32)	70	50
BT.30AD-CC.ER40.070	BT 30	3 – 26 (ER 40)	70	63
BT.30AD-CC.ER16.100	BT 30	1 – 10 (ER 16)	100	32
BT.30AD-CC.ER25.100	BT 30	2 – 16 (ER 25)	100	42
BT.30AD-CC.ER32.100	BT 30	2 – 20 (ER 32)	100	50
BT.40AD-CC.ER16.063	BT 40	1 – 10 (ER 16)	63	32
BT.40AD-CC.ER25.060	BT 40	2 – 16 (ER 25)	60	42
BT.40AD-CC.ER32.070	BT 40	2 – 20 (ER 32)	70	50
BT.40AD-CC.ER40.080	BT 40	3 – 26 (ER 40)	80	63
BT.40AD-CC.ER16.100	BT 40	1 – 10 (ER 16)	100	32
BT.40AD-CC.ER25.100	BT 40	2 – 16 (ER 25)	100	42
BT.40AD-CC.ER32.100	BT 40	2 – 20 (ER 32)	100	50
BT.40AD-CC.ER40.100	BT 40	3 – 26 (ER 40)	100	63

Delivery: With balanced clamping nut



DIN 69871

ISO 60

MAS 403 BT

DIN 2080

HSK-A

VDI

MORSE

